

Installation instructions

Self-adhesive tactile studs Ø 25 mm and strips 270 × 34 mm

Application

For quick installation of tactile marking on smooth, hard floors – marble, porcelain stoneware, polished concrete, ceramics – mainly indoors: corridors, lobbies, in front of lifts, counters and stairs. No drilling and no liquid adhesives. The layout is set by the project design in accordance with ISO 23599:2019 and the applicable national regulations.

Materials and tools

Self-adhesive studs or strips; layout template; degreasing agent (e.g. isopropyl alcohol); clean lint-free cloths; masking tape or marker; rubber mallet or roller.

Step-by-step installation

1	Prepare the surface The surface must be smooth, hard, dry, dust-free and degreased. Clean it, degrease it and let it dry completely.
2	Mark out Mark the area with tape or a marker and position the template. Strips are laid parallel, in the walking direction (4 strips for a 30 × 30 cm field, 5 strips for a 40 × 30 cm field). Studs are placed in a grid following the template – 25 studs (5 × 5) for a 30 × 30 cm field and 49 studs (7 × 7) for a 40 × 40 cm field.
3	Remove the release liner Peel off the release liner from the base without touching the adhesive surface with your fingers.
4	Stick down Place each element exactly on the template and press it firmly over its whole surface (by hand, rubber mallet or roller).
5	After installation Remove the template and the marking. Keep the installation dry and unloaded until the bond has stabilised.

Maintenance

Clean with a damp cloth and a neutral detergent. Do not use solvents or abrasive cleaners. Damaged elements can be replaced individually.

Important: do not install on wet, dusty, crumbling or very rough surfaces – this reduces adhesion.

The relief and dimensions of the self-adhesive studs and strips are designed in accordance with ISO 23599:2019.